ViziPrint®

Deco SR

CREATE ARCHITECTURAL APPLICATIONS

This optically clear scratch-resistant printable window film utilises a special ink-receptive top coat for greater adhesion of inks. ViziPrint® Deco SR is ideal for architectural applications where decorative glass details are needed to create dynamic spaces, including conference rooms or private meeting areas. It can also be used to create graphics and window decals for retail storefronts and POP or backlit displays.

- IDEAL FOR HIGH QUALITY GRAPHICS FOR HIGH END RETAIL STOREFRONTS
- SUITABLE FOR CONFERENCE ROOMS AND ARCHITECTURAL APPLICATIONS.

2 mil Clear Transparent PET

☐ Gloss

UV Latex

Clear Permanent Acrylic (Pressure Sensitive)

Widths up to 61 in

7 YEARS DURABILITY **INTERIOR**

3 YEARS DURABILITY **EXTERIOR**





APPLICATIONS

Smooth Flat Surfaces

Retail Backlit Displays

Window Graphics

Decals & Stickers

Certified for **HP Latex Inks**

This media may not be certified for all HP Latex ink and printing systems. Please check the HP media locator website at hp.com/go/mediasolutionslocator

DRYTAC®

ADHESIVE SCIENCE

ViziPrint®

Deco SR

TECHNICAL SPECIFICATION

ViziPrint® Deco SR is a 50µ (2 mil) scratch-restistant optically clear gloss PET film, coated with a permanent clear acrylic adhesive and protected by a siliconised PET release liner that has a super smooth profile to enhance the clarity when applied to glass. It has a special top coat to enhance the adhesion of inks. The film's high quality adhesive adheres to most substrates.

- IDEAL FOR HIGH QUALITY GRAPHICS FOR HIGH END RETAIL STOREFRONTS
- SUITABLE FOR CONFERENCE ROOMS AND ARCHITECTURAL APPLICATIONS.

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application. Use gloves to avoid fingerprints. Wet installation is recommended.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

PRODUCT STRUCTURE

Film	Scratch-Resistant Gloss Transparent PET with Ink-Receptive Top Coat
Adhesive	Clear Permanent Acrylic (Pressure Sensitive)
Release Liner	Siliconised 1 Side PET

PRODUCT CHARACTERISTIC

Film Thickness	2 mil (50µ)
Adhesive Layer	0.8mil (20µ)
	2.8 mil (70µ)
Film/Adhesive Ratio	2:0.8
UV Protection Factor	Not Applicable
Outdoor Durability	3 Years
Application Temperature	>41˚F (5˚C)
Service Temperature Range	-4˚F to 266˚F (-20˚C to 130˚C)
Shelf Life	2 years
Storage Conditions	59˚F to 72˚F (15˚C to 22˚C); 50 - 55% Relative Humidity

DRYTAC®
ADHESIVE SCIENCE

Europe
Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada
105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA
5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013