Protac™

Floortex 200

TECHNICAL SPECIFICATION

Protac™ Floortex 200 is a 8 mil (200µ) monomeric calendared PVC protective laminating film with a scuff-resistant, textured matte finish, coated on one side with a pressure sensitive, solvent acrylic adhesive that is protected by a single side siliconised PE coated Kraft release liner.

- RECOMMENDED FOR LAMINATING PRINT MEDIA TO CREATE DURABLE FLOOR GRAPHICS, BOTH INDOOR AND OUTDOORS.
- IDEAL FOR FLOOR GRAPHICS, EVENT SIGNAGE, TRADESHOW GRAPHICS, POP DISPLAYS, COUNTER MATS, MOUSE MADS AND OTHER SIGNAGE WHERE A SCUFF-RESISTANT FINISH IS REQUIRED.
- CAN BE COMBINED WITH DRYTAC'S FLOORTAC PRINT MEDIA FOR INDOOR FLOOR GRAPHICS OR DRYTAC'S POLAR GRIP FOR OUTDOOR FLOOR GRAPHICS.

* Outdoor floor durability is 12 months dependant upon floor traffic and proper installation.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

PRODUCT STRUCTURE

Film	Matte Textured Monomeric Calendared PVC
Adhesive	Permanent Solvent Acrylic (Pressure Sensitive)
Release Liner	135gsm 1 Side Siliconised PE Coated Kraft

PRODUCT CHARACTERISTICS

Film Thickness	8 mil (200µ)
Adhesive Layer	0.8 mil (20µ)
UV Protection Factor	Yes
Outdoor Durability	12 months*
Slip Rating (EN 13036-4) Pendulum Test Value (PTV)	Low Slip Potential 72 Dry; 41 Wet
Fire Rating	Class 0 (BS 476 Part 6 and 7)
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)
Application Temperature	>41°F (5°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC®
ADHESIVE SCIENCE

Europe
Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada
30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA
5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013