SpotOn®

SPOM54164 - MT - Drytac Matt-Bubble Free Vinyl

EASY BUBBLE FREE APPLICATION

SpotOn® has a unique dot pattern removable adhesive that is virtually undetectable, but allows graphics to be installed with minimal effort, remain in place for the duration of the application, and removed with ease. The film's adhesive allows for easy, bubble-free application of vibrant graphics to a wide range of substrates without the need for tools or wet installation. Available in clear matte, clear gloss, white matte and white gloss finishes. SpotOn® is commonly used for window graphics but can also be used for short-term indoor applications such as wall graphics, tradeshow graphics or retail graphics that require seasonal change out.

- IDEAL FOR INDOOR OR SHORT-TERM OUTDOOR PROMOTIONS
- EASY TOOL & BUBBLE FREE APPLICATION
- CAN BE REMOVED EASILY WITHIN 12 MONTHS

Product Code: SPOG, SPOM, SPOT, SPOC

100 micron Clear or White Monomeric PVC

Matte or Gloss

(Eco)Solvent
Latex
UV

DOT Pattern
Removable
Adhesive

Widths up to 1370mm

3 YEARS DURABILITY **INTERIOR**

6 MONTHS DURABILITY **EXTERIOR**





APPLICATIONS

Indoor Signage

Retail Promotions

Window Graphics

Certified for **HP Latex Inks**

MIDCOMP CONSUMABLES

DRYTAC ADHESIVE SCIENCE

010 020 9999 consumables@midcomp.co.za www.midcomp.co.za/consumables

SpotOn®

MIDCOMP CONSUMABLES

TECHNICAL SPECIFICATION

SpotOn® is a 100µ (4 mil) printable monomeric PVC film with a dot pattern, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single-sided, siliconised clay coated Kraft release liner. This high quality, ink receptive printable vinyl was specifically developed for easy, bubble-free application of vibrant graphics to a wide range of substrates. SpotOn® is available in clear matte, clear gloss, white matte and white gloss finishes.

- PROP 65 COMPLIANT
- EASY TOOL & BUBBLE FREE APPLICATION
- CAN BE REMOVED EASILY WITHIN 12 MONTHS

INSTALLATION RECOMMENDATION

Please see SpotOn® installation instructions for further details. The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

PRODUCT STRUCTURE

Film	Clear Matte, Clear Gloss, White Matte or White Gloss Monomeric PVC
Adhesive	Dot-Pattern Removable Polyacrylate
Release Liner	140 gsm 1 Side Siliconised PE Coated Kraft

PRODUCT CHARACTERISTIC

Film Thickness	4 mil (100µ)	4.5 mil (113µ)
Adhesive Layer	0.5 mil (13µ)	
Film/Adhesive Ratio	4:0.5	
UV Protection Factor	Not Applicable	
Outdoor Durability	Short-Term	
Application Temperature	>41˚F (5˚C)	
Service Temperature Range	-4˚F to 149˚F (-20˚C to 65˚C)	
Flame Retardancy	B1 (According to DIN 4102-1)	
Shelf Life	1 year	
Storage Conditions	64˚F to 77˚F (18˚C to 25˚C); 40 - 65% Relative Humidity	

MIDCOMP CONSUMABLES

DRYTAC® ADHESIVE SCIENCE

Johannesburg
Unit 21, Hylauma Street,
Fern Towers, Ferndale,
Randburg, Gauteng
South Africa
consumables@midcomp.co.za
Tel: +27 (0) 10 020 9999

Cape Town
Unit 1, 4 Platinum Close,
Phoenix, Cape Town
Western Cape,
South Africa
cptorders@midcomp.co.za
Tel: +27 (0) 21 552 3453

Durban
Unit 1, Janic Park,
30 Moreland Drive, Redhill
Durban, Kwa-Zulu Natal,
South Africa
consumables@midcomp.co.za
Tel: +27 (0) 10 020 9999